EVVA AirKey Proximity Wall Reader

Controllers & Readers · Evva · 6 variants

PRICING

From £422.06 ex VAT

£506.47 inc VAT

6 variants available
VAT 20.00%
Range: £422.06 - £485.55 ex VAT

Product Imagery

















Specification Summary

Brand	Evva
Product type	Controllers & Readers

Product Description

The EVVA AirKey Proximity Wall Reader combines superior design with high-quality materials to deliver an attractive, sleek, and highly practical access control solution. Designed to be used in conjunction with the AirKey Wall Reader Control Unit, this reader is suitable for controlling electronic locking components in a wide variety of applications, including sliding and swinging doors, lifts, and turnstiles.

This versatile reader is available in multiple finishes, including Black, Silver, and White, as well as both Flush (15mm depth) and Surface (31mm depth) fitting options to suit your installation requirements. Please choose your preferred finish, fitting type, and depth from the options below.

Engineered for durability, the unit features an IP65 weatherproof rating and a wide operating temperature range of -25°C to +70°C, making it ideal for both indoor and outdoor installations. It is easy to install with no special assembly tools required and comes complete with all necessary seals and fixings.

Technical Specifications

- **Brand:** Evva
- **Format:** Proximity & NFC
- **Fitting Type:** Flush or Surface (please choose from the options below)
- **Depth:** 15mm or 31mm (please choose from the options below)
- **Finish:** Black, Silver, or White (please choose from the options below)
- **Manufacturer Reference:** E.A.WL.RU (Flush) or E.A.WL.RA (Surface) (please choose from the options below)
- **IP Rating:** IP65 (Weatherproof)
- **Operating Temperature:** -25°C to +70°C
- **Humidity:** < 90%, non-condensing
- **Audit Trail:** Last 1,000 events
- **Connections:** Terminals (maximum 100m Cat 5 cable between reader and control unit)
- **Visual Indication:** Yes
- **Width:** 80.5mm
- **Weight:** 356g
- **Standards:** CE Marked

Key Features

- **Sleek Design:** Features an attractive 4mm glass front panel with a slim profile.
- **Weatherproof Protection:** IP65 rated and suitable for both indoor and outdoor use.
- **Versatile Applications:** Ideal for controlling electronic locking components on sliding doors, turnstiles, lifts, and revolving doors.
- **Control Unit Integration:** Designed specifically for use with the AirKey Wall Reader Control Unit.
- **Simple Installation:** Easy to install with no special assembly tools required.
- **Complete Kit:** Supplied complete with all required seals and fixings.

Variant Specifications And Pricing

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L31684	£422.06	£506.47	**Audit Trail:** Last 1,000 events **Barcode:** 5056240120690 **Brand:** Evva **Connections:** Terminals **Controller Required:** Yes **Depth:** 15mm **Finish:** Black **Fitting:** Flush **Format:** Proximity & NFC **Humidity:** Humidity < 90 %, non-condensing **IP Rating:** IP65 **Manufacturer Reference:** E.A.WL.RU **Notes:** Max 100m Cat 5 cable between reader and control unit **Operating Temperature:** -25°C to 70°C **Pack Quantity:** 1 **Stand Alone Or Networked:** Network **Standards:** CE Marked **Visual Indication:** Yes **Weight:** 356g **Width:** 80.5mm
	L31685	£422.06	£506.47	**Audit Trail:** Last 1,000 events **Barcode:** 5056240120706 **Brand:** Evva **Connections:** Terminals **Controller Required:** Yes **Depth:** 15mm **Finish:** White **Fitting:** Flush **Format:** Proximity & NFC **Humidity:** Humidity < 90 %, non-condensing **IP Rating:** IP65 **Manufacturer Reference:** E.A.WL.RU **Notes:** Max 100m Cat 5 cable between reader and control unit **Operating Temperature:** -25°C to 70°C **Pack Quantity:** 1 **Stand Alone Or Networked:** Network **Standards:** CE Marked **Visual Indication:** Yes **Weight:** 356g **Width:** 80.5mm

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L31686	£422.06	£506.47	**Audit Trail:** Last 1,000 events **Barcode:** 5056240120713 **Brand:** Evva **Connections:** Terminals **Controller Required:** Yes **Depth:** 15mm **Finish:** Silver **Fitting:** Flush **Format:** Proximity & NFC **Humidity:** Humidity < 90 %, non-condensing **IP Rating:** IP65 **Manufacturer Reference:** E.A.WL.RU **Notes:** Max 100m Cat 5 cable between reader and control unit **Operating Temperature:** -25°C to 70°C **Pack Quantity:** 1 **Stand Alone Or Networked:** Network **Standards:** CE Marked **Visual Indication:** Yes **Weight:** 356g **Width:** 80.5mm
	L31687	£485.55	£582.66	**Audit Trail:** Last 1,000 events **Barcode:** 5056240120720 **Brand:** Evva **Connections:** Terminals **Controller Required:** Yes **Depth:** 31mm **Finish:** Black **Fitting:** Surface **Format:** Proximity & NFC **Humidity:** Humidity < 90 %, non-condensing **IP Rating:** IP65 **Manufacturer Reference:** E.A.WL.RA **Notes:** Max 100m Cat 5 cable between reader and control unit **Operating Temperature:** -25°C to 70°C **Pack Quantity:** 1 **Stand Alone Or Networked:** Network **Standards:** CE Marked **Visual Indication:** Yes **Weight:** 356g **Width:** 80.5mm

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L31688	£485.55	£582.66	**Audit Trail:** Last 1,000 events **Barcode:** 5056240120737 **Brand:** Evva **Connections:** Terminals **Controller Required:** Yes **Depth:** 31mm **Finish:** White **Fitting:** Surface **Format:** Proximity & NFC **Humidity:** Humidity < 90 %, non-condensing **IP Rating:** IP65 **Manufacturer Reference:** E.A.WL.RA **Notes:** Max 100m Cat 5 cable between reader and control unit **Operating Temperature:** -25°C to 70°C **Pack Quantity:** 1 **Stand Alone Or Networked:** Network **Standards:** CE Marked **Visual Indication:** Yes **Weight:** 356g **Width:** 80.5mm
	L31689	£485.55	£582.66	**Audit Trail:** Last 1,000 events **Barcode:** 5056240120744 **Brand:** Evva **Connections:** Terminals **Controller Required:** Yes **Depth:** 31mm **Finish:** Silver **Fitting:** Surface **Format:** Proximity & NFC **Humidity:** Humidity < 90 %, non-condensing **IP Rating:** IP65 **Manufacturer Reference:** E.A.WL.RA **Notes:** Max 100m Cat 5 cable between reader and control unit **Operating Temperature:** -25°C to 70°C **Pack Quantity:** 1 **Stand Alone Or Networked:** Network **Standards:** CE Marked **Visual Indication:** Yes **Weight:** 356g **Width:** 80.5mm

Brand Profile

Evva

EVVA is an Austrian, **family-owned** security manufacturer based in **Vienna**, specialising in high-end **mechanical and electronic locking systems** for everything from homes to large, complex master-keyed organisations. The company was **founded in Vienna in 1919**, and it still runs **research, development, and production** from its Vienna headquarters, exporting globally.

In the trade/spec world, EVVA's reputation is built on **serious key control** and **master key system engineering**—locks designed not just to resist attack, but to keep access hierarchies manageable at scale (offices, hospitals, residential complexes, universities, etc.).

A couple of EVVA's standout mechanical platforms get referenced constantly:

- **ICS (Inner Code System)** – a reversible key system aimed at **highly complex master key structures**, with EVVA citing long patent protection (into the 2030s, depending on jurisdiction).
- **MCS (Magnetic Code System)** – EVVA positions this as a top-tier system for sophisticated master keying, with a strong anti-copying story (including resistance to modern replication methods).

They also explicitly brand themselves around innovation: EVVA talks about holding **200+ patents** and frames its history as "start-up energy since 1919" (which is an absolutely deranged sentence for a century-old lock company, but I respect the audacity).