FREEMAN & PARDOE ARROW Series 600 Size 3 Hold Open Door Closer

Overhead · Freeman & Pardoe · 2 variants

PRICING

From £209.07 ex VAT

£250.88 inc VAT

2 variants available
VAT 20.00%
Range: £209.07 - £254.93 ex VAT

Product Imagery











Specification Summary

Brand	Freeman & Pardoe
Product type	Overhead

Product Description

Designed and manufactured in the UK, the Freeman & Pardoe Arrow Series 600 (Model 623) Size 3 Electromagnetic Door Closer represents a premium solution for fire door safety and barrier-free access. This versatile unit is ideal for environments like schools, hospitals, theatres, and care homes where ease of movement is essential.

The closer can be configured on-site to operate in either 'hold open' or 'free swing' mode. In Hold Open mode, it holds the door open to assist traffic flow, while in Swing Free mode, it allows the door to operate with virtually no resistance. When connected to the building's fire detection system, the closer automatically releases and closes the door securely upon fire detection. It features adjustable closing speed and latching action, allowing for a slower, safer closing motion.

This door closer is available in multiple finishes, including Satin Stainless Steel and Silver Enamelled. Please select your preferred finish and manufacturer reference from the options below.

Technical Specifications

- **Brand:** Freeman & Pardoe
- **Series:** Arrow 600 (Model 623)
- **Power Size:** Size 3
- **Max Door Weight:** 60kg
- **Max Door Width:** 950mm
- **Dimensions:** 27.8cm (Length) x 46mm (Depth)
- **Handing:** Reversible (non-handed)
- **Application:** Fig 1, Fig 6, and Fig 61
- **Standards & Certifications:** CE Marked, Certifire approved, BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300
- **Fire Rating:** Tested up to 120 minutes on timber doors

Key Features

- **UK Manufactured:** Designed and manufactured in the UK for reliable quality.
- **Dual Functionality:** On-site choice of 'hold open' or 'free swing' functions to suit building requirements.
- **Automatic Fire Closing:** Automatically closes the door upon fire detection when connected to the building's fire alarm system.
- **Adjustable Controls:** Fully adjustable closing speed and latching action.
- **Multiple Finishes:** Available in Satin Stainless Steel or Silver Enamelled finishes (please select below).
- **Ease of Access:** Helps buildings comply with accessibility guidelines and BS 8300 recommendations.

Variant Specifications And Pricing

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L25756	£209.07	£250.88	**Adjustable Closing Speed:** Yes **Adjustable Latch Action:** Yes **Application:** Fig 1, Fig 6 & Fig 61 **Barcode:** 5055120773957 **Brand:** Freeman & Pardoe **Depth:** 46mm **Finish:** Silver Enamelled **Fire Tested:** 2 Hours Timber **Handed:** Reversible **Hold Open:** Yes **Length:** 27.8cm **Manufacturer Reference:** 623 SE **Max Door Weight:** 60Kg **Max Door Width:** 950mm **Pack Quantity:** 1 **Packaging:** Boxed **Standards:** BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire **Strength Size:** 3 **Weight:** 3.54Kg
	L25758	£254.93	£305.92	**Adjustable Closing Speed:** Yes **Adjustable Latch Action:** Yes **Application:** Fig 1, Fig 6 & Fig 61 **Barcode:** 5055120773971 **Brand:** Freeman & Pardoe **Depth:** 46mm **Finish:** Satin Stainless Steel **Fire Tested:** 2 Hours Timber **Handed:** Reversible **Hold Open:** Yes **Length:** 27.8cm **Manufacturer Reference:** 623 SSS **Max Door Weight:** 60Kg **Max Door Width:** 950mm **Pack Quantity:** 1 **Packaging:** Boxed **Standards:** BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire **Strength Size:** 3 **Weight:** 3.54Kg

Brand Profile

Freeman & Pardoe



Freeman & Pardoe is a UK specialist manufacturer of **fire-door control products**, best known for the **Arrow** range of **door closers** and **electromagnetic hold-open / swing-free solutions** designed to balance **life-safety** with **accessibility**. They position their products around **passive fire protection**: keeping doors usable in day-to-day operation, while ensuring they **automatically close on fire alarm/power interruption** to maintain compartmentation.

The company emphasises that Arrow products are **designed, manufactured, and tested in Great Britain**, with a catalogue that includes:

- **Fire door closers** (conventional overhead closers for certified fire doors)
- **Electromagnetic hold-open closers** linked to the building's **fire detection system**, allowing doors to be held open legally for traffic flow and **barrier-free access**, then releasing to close on alarm
- Complementary items like **fire door signage**

On compliance, Freeman & Pardoe's Arrow products are commonly sold and specified with testing and standards alignment such as **BS EN 1154** (door closers), fire testing to **BS EN 1634**, and accessibility considerations tied to **BS 8300 / Approved Document M / Equality Act** expectations (you'll see these referenced across spec/distributor descriptions).