FREEMAN & PARDOE ARROW Series 600 Size 4 Hold Open Door Closer

Overhead · Freeman & Pardoe · 2 variants

PRICING

From £212.18 ex VAT

£254.62 inc VAT

2 variants available
VAT 20.00%
Range: £212.18 - £253.58 ex VAT

Product Imagery







Specification Summary

Brand	Freeman & Pardoe
Product type	Overhead

Product Description

Designed and manufactured in the UK, the Freeman & Pardoe Arrow Series 600 (Size 4) electromagnetic door closer represents a premium solution for fire door safety and barrier-free access. This versatile unit can be configured on-site for either 'hold open' or 'free swing' operation. When connected to a building's fire detection system, it automatically releases and closes the door upon fire detection, preventing the spread of smoke and flames.

With adjustable closing speed and latching action, this door closer is highly suited for environments such as hospitals, schools, care homes, and theatres, where a slower closing speed can assist less-abled users. It is non-handed (reversible) and suitable for Fig 1, Fig 6, and Fig 61 applications.

This door closer is available in multiple finishes, including Satin Stainless Steel and Silver Enamelled, with corresponding manufacturer references (624 SSS or 624 SE) and barcodes. Please choose your preferred finish and option from the selection below.

Technical Specifications

- **Brand:** Freeman & Pardoe (Arrow)
- **Power Size:** Strength Size 4
- **Max Door Width:** 1100mm
- **Max Door Weight:** 80kg
- **Dimensions:** 27.8cm (Length) x 46mm (Depth)
- **Weight:** 3.54kg
- **Application:** Fig 1, Fig 6, and Fig 61
- **Handing:** Reversible (Non-handed)
- **Fire Rating:** Fire tested up to 120 minutes (2 hours) on timber doors
- **Standards & Certifications:** CE Marked, Certifire approved, BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300
- **Finishes:** Available in Satin Stainless Steel or Silver Enamelled (please select from the options below)
- **Manufacturer References:** 624 SE / 624 SSS (please select from the options below)

Key Features

- **Dual Functionality:** On-site choice of electromagnetic 'hold open' or 'free swing' modes to assist with ease of access and traffic flow.
- **Automatic Fire Closing:** Automatically releases and closes the door upon fire detection when correctly connected to the building's fire alarm system.
- **Adjustable Controls:** Features adjustable closing speed and latching action to suit specific user requirements.
- **UK Manufactured:** Designed and manufactured in the UK by Freeman & Pardoe.
- **High Fire Safety Compliance:** Certifire approved and fire tested for up to 120 minutes on timber doors.
- **Versatile Mounting:** Non-handed design suitable for multiple mounting applications (Fig 1, Fig 6, and Fig 61).

Variant Specifications And Pricing

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L25759	£212.18	£254.62	**Adjustable Closing Speed:** Yes **Adjustable Latch Action:** Yes **Application:** Fig 1, Fig 6 & Fig 61 **Barcode:** 5055120773988 **Brand:** Freeman & Pardoe **Depth:** 46mm **Finish:** Silver Enamelled **Fire Tested:** 2 Hours Timber **Handed:** Reversible **Hold Open:** Yes **Length:** 27.8cm **Manufacturer Reference:** 624 SE **Max Door Weight:** 80Kg **Max Door Width:** 1100mm **Pack Quantity:** 1 **Packaging:** Boxed **Standards:** BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire **Strength Size:** 4 **Weight:** 3.54Kg
	L25761	£253.58	£304.30	**Adjustable Closing Speed:** Yes **Adjustable Latch Action:** Yes **Application:** Fig 1, Fig 6 & Fig 61 **Barcode:** 5055120774008 **Brand:** Freeman & Pardoe **Depth:** 46mm **Finish:** Satin Stainless Steel **Fire Tested:** 2 Hours Timber **Handed:** Reversible **Hold Open:** Yes **Length:** 27.8cm **Manufacturer Reference:** 624 SSS **Max Door Weight:** 80Kg **Max Door Width:** 1100mm **Pack Quantity:** 1 **Packaging:** Boxed **Standards:** BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire **Strength Size:** 4 **Weight:** 3.54Kg

Brand Profile

Freeman & Pardoe



Freeman & Pardoe is a UK specialist manufacturer of **fire-door control products**, best known for the **Arrow** range of **door closers** and **electromagnetic hold-open / swing-free solutions** designed to balance **life-safety** with **accessibility**. They position their products around **passive fire protection**: keeping doors usable in day-to-day operation, while ensuring they **automatically close on fire alarm/power interruption** to maintain compartmentation.

The company emphasises that Arrow products are **designed, manufactured, and tested in Great Britain**, with a catalogue that includes:

- **Fire door closers** (conventional overhead closers for certified fire doors)
- **Electromagnetic hold-open closers** linked to the building's **fire detection system**, allowing doors to be held open legally for traffic flow and **barrier-free access**, then releasing to close on alarm
- Complementary items like **fire door signage**

On compliance, Freeman & Pardoe's Arrow products are commonly sold and specified with testing and standards alignment such as **BS EN 1154** (door closers), fire testing to **BS EN 1634**, and accessibility considerations tied to **BS 8300 / Approved Document M / Equality Act** expectations (you'll see these referenced across spec/distributor descriptions).