PAC 20110 Mullion Proximity Reader Low Frequency

Pac · PAC · 1 variant

PRICING

From £166.81 ex VAT

£200.17 inc VAT

1 variant available
VAT 20.00%

Product Imagery



Specification Summary

Brand	PAC
Product type	Pac

Product Description

The PAC 20110 (909020110) OneProx GS3 Low Frequency (LF) Mullion Proximity Reader is a compact, highly durable access control reader designed for installation on door frames (mullions) or flat surfaces. Built to withstand demanding environments, this reader is IP65-rated, making it suitable for both indoor and outdoor installations.

This versatile reader supports all PAC LF ID devices (153.6kHz) and KeyPAC (125kHz) credentials, as well as many third-party Wiegand format tokens. It features a clear visual red/green LED lightbar and an audible sounder to provide immediate feedback on card reads. With an integral tamper circuit, it meets EN 50131-1 and EN 50131-3 standards, ensuring enhanced security for your premises.

Technical Specifications

- **Brand:** PAC
- **Manufacturer Reference:** 909020110
- **Format:** Proximity
- **Frequency:** LF (Low Frequency) - 125kHz and 153.6kHz
- **IP Rating:** IP65 (Weather resistant)
- **Dimensions:** 105mm (H) x 38mm (W) x 15mm (D)

- **Weight:** 200g
- **Finish:** Black
- **Fitting:** Surface mount
- **Controller Required:** Yes (such as PAC 20370)
- **Read Range:** Up to 85mm (depending on credential type)
- **Cabling Requirements:** Wiegand output requires 5-core 22 AWG cable; PAC output requires 6-core 24 AWG unscreened alarm cable
- **Standards:** UKCA, CE Marked, EN 50131-1 & EN 50131-3 (Tamper Output)

Key Features

- **Broad Compatibility:** Backwards compatible with EasiKey systems, supporting PAC and KeyPAC credentials as well as third-party Wiegand tokens.
- **Weatherproof Design:** IP65-rated polycarbonate housing makes it suitable for both indoor and outdoor installations.
- **Clear Feedback:** Built-in audible sounder and visual red/green LED indicators provide clear user confirmation.
- **Compact Mullion Profile:** Slim design is ideal for mounting directly onto door frames or flat surfaces.
- **Enhanced Security:** Features an integral tamper circuit to alert against unauthorized physical interference.
- **Reliable Performance:** Offers a read range of up to 85mm for fast, touch-free access.

Variant Specifications And Pricing

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L5243	£166.81	£200.17	**Audible Indication:** Yes **Barcode:** 5055120630441 **Brand:** PAC **Connections:** Terminals **Controller Required:** Yes - 20370 **Depth:** 15mm **Finish:** Black **Fitting:** Surface **Format:** Proximity **Frequency:** LF - 125kHz and 153.6kHz **Height:** 105mm **IP Rating:** IP65 **Manufacturer Reference:** 909020110 **Pack Quantity:** 1 **Packaging:** Boxed **Read Range:** Max 25mm **Stand Alone Or Networked:** Stand Alone **Standards:** UK Conformity Assessed (UKCA), CE Marked **Visual Indication:** Yes **Weather Resistant:** Yes **Weight:** 200g **Width:** 38mm

Brand Profile

PAC

No brand description provided.