

Declaration of Performance

CONSTRUCTION PRODUCTS REGULATION 2011
DECLARATION OF PERFORMANCE

No. 2022064

1. Unique identification code of the product-type:

Asec AS3100, AS3101, AS3102, AS3103, AS3104**Accessories: - AS4308, AS3107, AS3108 Outside Locking Devices.**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Asec AS3100, AS3101, AS3102, AS3103, AS3104

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**For use on fire and smoke compartmentation doors
Or
Locked doors on Escape routes**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Aldridge Security
Ltd, Unit H,
Redfern Park Way,
Birmingham,
B11 2BF
United Kingdom**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1125: 2008
Notified Certification body No.1121 performed the type testing and issued test reports.
Certificate of Constancy of Performance - 2812-CPR-AAA7799**

8. European Technical Assessment:

N/A

9. Declared performance

Essential characteristics	Performance	Harmonised technical Specification
Clause 4.2.1 Ability to release (for doors on escape routes)		EN 1125:2008
Release function Panic exit device mounting Exposed edges and corners Double doorset Bar installation Bar length Bar projection Bar end Operating bar face Test rod Door face gap	< 1 sec Pass > 0,5 mm Pass Z < 150 mm from frame stop > 60% of max door width W < 100 mm or 150 mm Pass > 18 mm Pass > 25 mm	

Accessible gap Door free movement Top vertical bolt Keepers Keepers dimensions Door mass and dimensions Outside access device Release forces Security requirement	Pass Pass Pass- (AS3100 Annex A & AS3104 Annex B Only) Pass Pass- (AS3100 Annex A & AS3104 Annex B Only) Door mass $\leq$ 200 Kg, door height $\leq$ 2520 mm, door width $\leq$ 1320 mm Pass < 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N. Grade 2	
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes)		
Corrosion resistance Temperature range Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance –Horizontal bar Abuse resistance –Vertical rod Final examination	Grade 3: 96 h Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 1 000 N 500 N - (AS3100 Annex A & AS3104 Annex B Only) < 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N	
Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes)		
Re-engagement force	< 50 N	
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes)		
Durability Re-engagement force	Grade 7: 200 000 cycles < 50 N	
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes)		
Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B: Suitable for use on fire/smoke door assemblies	
Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

Asec Product	Single Door (Standard Keeper)	Double Door (Standard Keepers)				
ANNEX A						
AS3100	✓	✓	-----	-----	-----	-----
ANNEX B						
AS3104	-----	✓	-----	-----	-----	-----
ANNEX C						
AS3102	-----	✓	-----	-----	-----	-----
Accessories						
Model Number		Description				
Asec AS3107		Lever outside access device (Suitable for use with all devices)				
Asec AS3108		Knob outside access device (Suitable for use with all devices)				
Asec AS4308 Digital Device		Lever outside access device (Suitable for use with all devices)				
AS1428 AS1181 Rim Cylinder		Rim cylinder for use with AS3102 only				

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Chris Thorpe Dip GAI Minst AI Product Manager

Aldridge Security Ltd,
Unit H,
Redfern Park Way,
Birmingham,
B11 2BF
United Kingdom
24th June 2022