


Applic

- surface-mounted drop seal
- concealed screws and slide-on cover profile



TECHNICAL DATA

Application	hinged timber, metal & PVC doors
Actuation	single
Gasket material	TPE

DIMENSIONS

Width x height	13 x 49 mm
Standard lengths	customized
Minimum lengths*	320 mm
Maximum lengths	1200 mm
Can be shortened by	125 mm, smallest product length that can be shortened: 445 mm
Travel	15 mm

FIXING

Fixing	surface mounted to the face of the door, screw fixed
--------	--

PERFORMANCE & CERTIFICATES

Acoustic	in accordance with DIN EN ISO 10140-2 achieving a rating of up to 38dB _{RW}
Fire	BS EN 1634-1
Smoke	BS EN 1634-3: 2004

ARTICLE CODES

FS785	330 mm Applic Drop Down Seal	FS790	830 mm Applic Drop Down Seal
FS786	430 mm Applic Drop Down Seal	FS791	930 mm Applic Drop Down Seal
FS787	530 mm Applic Drop Down Seal	FS792	1030 mm Applic Drop Down Seal
FS788	630 mm Applic Drop Down Seal	FS793	1130 mm Applic Drop Down Seal
FS789	730 mm Applic Drop Down Seal	FS794	1230 mm Applic Drop Down Seal

* min. lengths cannot be shortened