

FREEMAN & PARDOE ARROW Series 600 Size 5 Hold Open Door Closer

Overhead · Freeman & Pardoe · 2 variants

PRICING

From £243.23 ex VAT

£291.88 inc VAT

2 variants available
VAT 20.00%

Range: £243.23 - £254.61 ex VAT

Product Imagery



Specification Summary

Brand	Freeman & Pardoe
Product type	Overhead

Product Description

Designed and manufactured in the UK, the Arrow Series 600 Size 5 Hold Open Door Closer from Freeman & Pardoe represents the ultimate in fire door safety and ease of access. This high-performance electromagnetic overhead door closer is ideal for high-traffic environments such as hospitals, schools, theatres, and care homes, where occupants benefit from a slower, controlled closing speed.

The Series 600 can be configured on-site to operate in either 'hold open' or 'free swing' mode. When connected to the building's 24V DC fire detection system, it allows fire doors to be held open safely or to swing freely without resistance during normal operation. In the event of a fire alarm activation or power interruption, the closer automatically releases, ensuring the door closes securely to prevent the spread of fire and smoke.

This non-handed closer features both adjustable latching action and closing speed, making it highly adaptable to your specific installation requirements. It is available in multiple finishes, including Satin Stainless Steel and Silver Enamelled, with corresponding manufacturer references (625 SSS and 625 SE). Please choose your preferred finish and manufacturer reference from the options below.

Technical Specifications

- **Brand:** Freeman & Pardoe
- **Power Size:** Size 5
- **Application:** Fig 1, Fig 6, and Fig 61
- **Maximum Door Weight:** 100kg
- **Maximum Door Width:** 1250mm
- **Fire Tested:** 2 hours (120 minutes) on timber doors
- **Handing:** Reversible (non-handed)
- **Hold Open Function:** Yes (electromagnetic)
- **Adjustable Closing Speed:** Yes
- **Adjustable Latch Action:** Yes
- **Dimensions:** 33cm (Length) x 47mm (Depth)
- **Weight:** 3.59kg
- **Standards:** BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire Approved
- **Finishes:** Available in Satin Stainless Steel or Silver Enamelled (please choose from the options below)
- **Manufacturer References:** Available as 625 SSS or 625 SE (please choose from the options below)

Key Features

- **Dual Operational Modes:** Configurable on-site for either 'hold open' or 'free swing' functionality.
- **Automatic Fire Closing:** Automatically releases and closes the door upon fire alarm activation when connected to the building's fire detection system.
- **Enhanced Accessibility:** Ideal for schools, hospitals, theatres, and residential homes where occupants benefit from a slower closing speed.
- **Fully Adjustable:** Features adjustable latching action and closing speed to suit specific door requirements.
- **UK Made:** Designed and manufactured in the UK to high standards of quality and reliability.

Variant Specifications And Pricing

Image	Part Number	Ex VAT	Inc VAT	Attributes / Specs
	L25762	£243.23	£291.88	Adjustable Closing Speed: Yes Adjustable Latch Action: Yes Application: Fig 1, Fig 6 & Fig 61 Barcode: 5055120774015 Brand: Freeman & Pardoe Depth: 47mm Finish: Silver Enamelled Fire Tested: 2 Hours Timber Handed: Reversible Hold Open: Yes Length: 33cm Manufacturer Reference: 625 SE Max Door Weight: 100Kg Max Door Width: 1250mm Pack Quantity: 1 Packaging: Boxed Standards: BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire Strength Size: 5 Weight: 3.59Kg
	L25764	£254.61	£305.53	Adjustable Closing Speed: Yes Adjustable Latch Action: Yes Application: Fig 1, Fig 6 & Fig 61 Barcode: 5055120774039 Brand: Freeman & Pardoe Depth: 47mm Finish: Satin Stainless Steel Fire Tested: 2 Hours Timber Handed: Reversible Hold Open: Yes Length: 33cm Manufacturer Reference: 625 SSS Max Door Weight: 100Kg Max Door Width: 1250mm Pack Quantity: 1 Packaging: Boxed Standards: BS EN 1154, BS EN 1155, BS EN 1634-1, BS EN 1634, BS EN 8300, CE Marked, Certifire Strength Size: 5 Weight: 3.59Kg

Brand Profile

Freeman & Pardoe



Freeman & Pardoe is a UK specialist manufacturer of **fire-door control products**, best known for the **Arrow** range of **door closers** and **electromagnetic hold-open / swing-free solutions** designed to balance **life-safety** with **accessibility**. They position their products around **passive fire protection**: keeping doors usable in day-to-day operation, while ensuring they **automatically close on fire alarm/power interruption** to maintain compartmentation.

The company emphasises that Arrow products are **designed, manufactured, and tested in Great Britain**, with a catalogue that includes:

- **Fire door closers** (conventional overhead closers for certified fire doors)
- **Electromagnetic hold-open closers** linked to the building's **fire detection system**, allowing doors to be held open legally for traffic flow and **barrier-free access**, then releasing to close on alarm
- Complementary items like **fire door signage**

On compliance, Freeman & Pardoe's Arrow products are commonly sold and specified with testing and standards alignment such as **BS EN 1154** (door closers), fire testing to **BS EN 1634**, and accessibility considerations tied to **BS 8300 / Approved Document M / Equality Act** expectations (you'll see these referenced across spec/distributor descriptions).